

Hardware implementation of safety smart password based GSM module controlling circuit breaker

Rakesh G. Shriwastava¹, Pawan C. Tapre², Rajendra M. Rewatkar³, Swapna M. Choudhary⁴,
Ramesh K. Rathod⁵, Sham H. Mankar⁶, Hemant R. Bhagat Patil⁶, Salim A. Chavan⁷

¹Department of Electrical Engineering, Govindrao Wanjari College of Engineering and Technology, Nagpur, India

²Department of Electrical Engineering, S.N.D. College of Engineering and Research Center, Yeola, India

³Biomedical Engineering Department, Faculty of Engineering and Technology, Datta Meghe Institute of Higher Education and Research, Wardha, India

⁴Department of Electronics and Telecommunications Engineering, G. H. Raisoni College of Engineering, Nagpur, India

⁵Department of Mechanical Engineering, PCET's Pimpri Chinchwad College of Engineering and Research, Pune, India

⁶Department of Mechanical Engineering, Govindrao Wanjari College of Engineering and Technology, Nagpur, India

⁷Department of Electronics and Telecommunication Engineering, Govindrao Wanjari College of Engineering and Technology, Nagpur, India

Article Info

Article history:

Received Jul 24, 2024

Revised Dec 13, 2024

Accepted Jan 19, 2025

Keywords:

ATmega328p microcontroller
Circuit breaker controlling
GSM
Lineman safety
Password security

ABSTRACT

This research work highlights the hardware implementation of safety smart password-based GSM module controlling circuit breaker. Safety is the major concern in daily life for domestic activities. In current scenario, accidental death of a lineman are the major issues and to protect operators for the same. To control circuit breakers, passwords security is essential for lineman. Due to that electrical accident's ratio is increased day to day life at the time of repairing the lines. It is also done due to lack of communication and coordination between maintenance and substation. For safety of lineman, on and off line turning operation is proposed. Secure password is for breaker operation and maintenance. In the proposed system, password is sent to the line operator's mobile phone and GSM module by automatic voltage regulator (AVR) microcontroller. Entered password and password received by the GSM receiver is match so circuit breaker will be smoothly operated. If password is incorrect, message will appear on the LCD display for security purposed and message sent to control room regarding unauthorized access to the system.

This is an open access article under the [CC BY-SA](https://creativecommons.org/licenses/by-sa/4.0/) license.



Corresponding Author:

Rakesh G. Shriwastava

Department of Electrical Engineering, Govindrao Wanjari College of Engineering and Technology
Nagpur, India

Email: rakesh_shriwastava@rediffmail.com

1. INTRODUCTION

In proposed system, electrical circuit's circuit breakers is projected from damage due to overloads or short circuits. To detect faults and block current flow is the major objective of circuit breaker [1]-[4]. The circuit breakers can be reset manually or automatically by replacing fuses. The ratio of electrical accidents of linemen are more in manual operation due to lack of communication and coordination between maintenance and substation [5]-[8]. The circuit breakers are designed using a secure password to avoid such incidents [9]-[15]. The design of 8-bit microcontroller from the ATmega328P family can be and fully controlled the operation of password circuit breakers. The password can change any time during operation and stored in microcontroller which is stored inside the microcontroller under electrically erasable programmable read-only memory (EEPROM) [16]-[20]. The password entering for circuit breaker operation, keypad is used.

The buzzer will sound an alarm if you enter the incorrect password [21]-[25]. In the proposed system, this model is designed for circuit breaker control, lineman safety, and maintenance point of view. If any fault occurs lineman enters the password to turn off the power supplied to the line and system repairs quickly. Figure 1 indicates the block diagram of smart safety with a password-based GSM module.




Figure 1. Block diagram of smart safety with password based GSM module

2. LITERATURE SURVEY

A comprehensive literature survey has been conducted to understand the existing research related to the proposed work. This survey includes various studies that focus on different aspects of circuit breaker control and monitoring systems. The following are some of the key research papers that have been reviewed, highlighting their methodologies, technologies used, and contributions to the field.

Kirti *et al.* [1] reviewed in paper title “Password based circuit breaker” that to control the circuit breaker, only specified password used and also provision of changing the password. For the program memory, 8-bit microcontroller 8051 family which has an 8 KB of ROM is used for controlling. For password entering matrix keypad is interfaced to the microcontroller and relay IC driver is used to switch the loads through relays. Step down transformer (230/12 V), is used to down the voltage to 12 V AC and is converted to DC using a bridge rectifier with capacitive filter for removed ripples. The voltage regulator (+5 V) is used for microcontroller and other components.

Kharat *et al.* [2] reviewed in paper title “Internet of thing (IoT) base controlling and monitoring of circuit breaker” that modern control centers system operators get alarm messages from many devices in real time. From alarms, it is still very hard to find out location and type of the potential equipment problem. One needs an automatic way of processing the events to identify whether sequences of equipment operation were as expected. Instead of many alarm messages, only one report should be sent to the operators with concise information about success or failure of a switching sequence. In the case of breaker, report will offer more detailed message whether the breaker failure logic worked out properly and finally disconnected faulted section. This kind of analysis enables tracking of every circuit breaker (CB) operation allowing reconstruction of an entire sequence of operations. In our project we studied designed to attain real time control and monitoring of circuit breaker. Measure and record loading of your output of CB and prevent overloading and increasing whole system life.

Nair *et al.* [3] reviewed in paper title “Electric line man safety system with OTP based circuit breaker” of International Journal of Research in Engineering and Technology that for lineman safety while working, sudden electric shock does not feel. The chances of critical accidents are already very high due to live wires and poor coordination between lineman and substation. This paper gives the solution for safety of maintenance staff and the lineman detect the fault in the electric line by SMS will be sent to the substation staff for switch off/on the line and fully operated on a microcontroller.

3. PROBLEM STATEMENT

Based on the literature survey, the key problem areas have been identified. One major concern is preventing unauthorized access and accidental activation of circuit breakers to mitigate electrical hazards and ensure safe working conditions for personnel. Additionally, enhancing safety for line workers during maintenance is crucial to ensure that circuit breakers remain deactivated until tasks are completed, reducing the risk of electrical shocks or injuries. Another critical issue is protecting sensitive equipment and systems from unauthorized tampering to secure critical infrastructure and prevent potential damage or disruptions.

4. OBJECTIVES OF PROJECT

The objectives of this project focus on enhancing security, enabling remote control, providing real-time monitoring, reducing costs, and ensuring seamless system integration. Enhanced security is achieved by preventing unauthorized access through password protection, safeguarding against tampering and accidental activation, particularly in hazardous environments, and improving electrical safety for personnel. Remote control allows operation of the circuit breaker from any location with GSM coverage, facilitating troubleshooting, maintenance, and load management without requiring physical presence, thereby offering flexibility and convenience. Real-time monitoring enables tracking of the circuit breaker's status, receiving alerts for unauthorized access attempts or abnormal conditions, and implementing preventive measures for prompt responses. Cost reduction is addressed by minimizing the need for manual intervention and site visits, reducing travel expenses, and optimizing resource allocation. Finally, system integration ensures compatibility with other systems, such as home automation and building management, fostering a more interconnected and efficient smart environment.

5. METHODOLOGY

5.1. Existing methods

In existing method, a lineman needs to visit power station and inform the in charge to ON/OFF. Then station in charge can be the inform to station operator and after the official procedure the line will be ON/OFF. But these methods were so old. There are the after latest technology give the password base method or finger prints scanner method so different types of method to operated but sometime loss connectivity lost signal or unskilled worker through likely not properly communicating so propose system give surety of controlling circuit breaker fully security based ON/OFF.

5.2. Proposed methodology

The proposed system methodology provides a solution to ensure worker and safety. The line ON/OFF control is performed only by the line operator. This system is designed to require a password to control the circuit breaker ON/OFF. The lineman can switch off the power and make repairs comfortably, and can also turn the line back on by entering the correct password after returning to the substation. Since you can change your password, you can set your desired password and work more safely. In the proposed system, control (ON/OFF) of the wire is assigned to the line operator. The project is designed in such a way that maintenance personnel or linemen must enter a password to turn the wire on or off. Now, if there is a problem with the wire, the lineman enters the password to cut off the power supplied to the line and repairs the line comfortably. When the lineman arrives at the substation, the lineman supplies power to the line. This project uses a 4×3 keyboard to enter the password. Compare the entered password with the preset password. If the entered password is correct, the corresponding wire will turn on or off. In this project, each wire has a separate password. Switching on and off a line (circuit breaker) is represented by a load.

5.2.1. Components description

The following are the descriptions of the key components used in the system. The power supply consists of a transformer that converts electricity between different voltage levels. The AC and DC voltages are achieved by converting and combining transformers, allowing electricity to be transformed from high to low voltage and vice versa. The system requires power to operate, with the microcontroller specifically needing 5 V DC, which is obtained by rectifying, filtering, and regulating the incoming AC current using the 7805 IC. The relay is an electrically operated switch that changes its contact positions when current flows through its coil, generating a magnetic field that attracts a lever. It has two switch positions and functions as a double-throw (changeover) switch. The buzzer is a small, enclosed component mounted on a printed circuit board. It operates on DC voltage, typically ranging from 3 V to 28 V, depending on the model. The Microcontroller ATmega328P is an 8-bit microcontroller with 32 KB of on-chip flash memory for programming. It processes one time password (OTP) generation and determines whether to switch the relay based on password verification. Finally, the GSM modem operates wirelessly on a GSM network and

functions similarly to dial-up modems. It enables data transmission via radio waves and requires a SIM card for operation, allowing communication with GSM phones and other GSM-enabled devices.

5.2.2. Operation of architecture

Figure 1 shows the architectural block diagram of the proposed "Smart safety with password-based GSM module controlling circuit breaker." We devised a system that requires the lineman to transmit the OTP in the format 1234. This format is used to represent an OTP. The deactivation feeder numbers 1, 2, and 3 are where they stand. A lineman needs to generate a four-digit password that's protected. The same thing happens when a lineman needs to send the same password in '1234' to activate the feeder. The four-digit number must match to activate the line that has been disabled.

When the utility worker transmits this data via text message to the power station where the GSM module is installed, the main authority will receive another message at the same time containing the latest LC's specifics, in order to avoid difficulties in case the utility worker forgets the password or loses the password, as well as to save the particulars. The lineman can't do this without the boss's blessing. Even though he's trying to charge the line without notifying the operator, he's going to get caught because the operator's number will be fed into the program, giving them his complete information about the line charge.

6. HARDWARE IMPLEMENTATION AND RESULTS

Figure 2 shows the operation begins and enters the mobile number. Figure 3 shows sending the OTP and matching the OTP. Figure 4 shows selected breaker is ON. Figure 5 shows selected breaker is OFF. Figure 6 shows sending the breakers status for registered mobile number. Figure 7 indicates the status for registered mobile number. The implementation of a smart safety with a password-based GSM module controlling circuit breaker utilizing ATmega328P microcontroller, relay, keypad, LCD display, and printed circuit board would be result in a fully operational circuit breaker that necessitates the input of a password before permitting the flow of electrical current. The circuit breaker would be under the control of a microcontroller, with the password being inputted via a keypad. The LCD display would provide instructions to the user for inputting the correct password. Upon entering the correct password, the relay would be triggered, enabling the flow of electrical current in the event of an incorrect password input.



Figure 2. Operation begin and enter the mobile number



Figure 3. Sending the OTP and after match the OTP



Figure 4. Selected breaker is ON



Figure 5. Selected breaker is OFF



Figure 6. Sending the breakers status for registered mobile number



Figure 7. Receive the status for registered mobile number

7. CONCLUSION

This paper focus on hardware implementation of safety smart password-based GSM module controlling circuit breaker. Serious electrical accidents occur becoming increasingly, when repairing power lines. It is happening due to lack of communication and coordination between maintenance and substation

Hardware implementation of safety smart password based GSM module ... (Rakesh G. Shrivastava)

personnel. In the proposed system, the on and off line turning operation with the lineman to ensure the safety of linemen. For that, a secure password is required to operate the breaker operation and maintenance point of view. Modified GSM can be connected to internet of things (IoT). So, relay of any of the area operate and directly connected to server. We can also use wireless ultrasonic, PIR sensors, and SCADA system for easy trouble shoot and identify the fault location directly and can easily rectify in future. We can also use EPROMS for interfacing the circuit breaker from other location through wireless communication.

FUNDING INFORMATION

Authors state no funding involved.

AUTHOR CONTRIBUTIONS STATEMENT

This journal uses the Contributor Roles Taxonomy (CRediT) to recognize individual author contributions, reduce authorship disputes, and facilitate collaboration.

Name of Author	C	M	So	Va	Fo	I	R	D	O	E	Vi	Su	P	Fu
Rakesh G. Shriwastava	✓	✓	✓	✓	✓	✓		✓	✓	✓		✓	✓	
Pawan C. Tapre		✓				✓		✓	✓	✓	✓	✓		
Rajendra M. Rewatkar	✓		✓	✓		✓	✓		✓	✓	✓		✓	✓
Swapna M. Choudhary	✓		✓			✓	✓		✓	✓			✓	
Ramesh K. Rathod	✓		✓			✓			✓	✓		✓		✓
Sham H. Mankar	✓	✓		✓		✓	✓		✓	✓		✓		
Hemant R. Bhagat Patil	✓			✓		✓			✓	✓		✓		✓
Salim A. Chavan		✓				✓	✓		✓	✓		✓		✓

C : Conceptualization

M : Methodology

So : Software

Va : Validation

Fo : Formal analysis

I : Investigation

R : Resources

D : Data Curation

O : Writing - Original Draft

E : Writing - Review & Editing

Vi : Visualization

Su : Supervision

P : Project administration

Fu : Funding acquisition

CONFLICT OF INTEREST STATEMENT

Authors state no conflict of interest.

DATA AVAILABILITY

Data availability is not applicable to this paper as no new data were created or analyzed in this study.




REFERENCES

- [1] M. M. Kirti, U. A. Arifa, A. D. Aishwarya, S. G. Pragati, and P. J. Sujit, "Password based circuit breaker," *International Journal for Research in Applied Science and Engineering Technology*, vol. 6, no. 4, pp. 2229–223, Apr. 2018, doi: 10.22214/ijraset.2018.4380.
- [2] B. Kharat, D. Sarwade, D. Bidgar, and B. Kadu, "Internet of thing (IoT) base controlling & monitoring of circuit breaker," *International Research Journal of Engineering and Technology (IRJET)*, vol. 04, no 05, pp. 668–673, May 2017.
- [3] A. P. Nair, J. Josephin, A. S. Anjana, C. P. Athira, and S. J. Olickal, "Electric line man safety system with OTP based circuit breaker," *International Journal of Research in Engineering and Technology*, vol. 04, no. 15, pp. 23–26, 2015, doi: 10.15623/ijret.2015.0415006.
- [4] A. Das, K. Kalimuthu, and S. S. Biswas, "IOT based circuit breaker monitoring & control," *International Journal of Applied Engineering Research*, vol. 13, no. 10, pp. 7806–7810, 2018.
- [5] L. Devdas, S. V. G., A. Kottor, and J. Justin, "Automated circuit breaker with IOT interfacing," *IOSR Journal of Engineering (IOSRJEN)*, pp. 29–32, 2018.
- [6] B. O. Oyebola, "Password based electric load switching gear for the safety of lineman," *International Journal of Engineering Science Technologies*, vol. 1, no. 1, 2017, doi: 10.29121/IJOEST.v1.i1.2017.05.
- [7] M. Kaufmann and G. S. H. Jarret, "Role of protection," in *Power System Protection: Principles and Components*, London, UK: IET, 1995.
- [8] M. A. Dumitrescu, *Network protection & automation guide*. Paris, France: Alstom Grid, 2002.
- [9] L. Hewitson, M. Brown, and R. Balakrishnan, *Practical power systems protection*. Oxford, UK: Newnes, 2005.
- [10] N. S. Nise, *Control systems engineering*, 6th ed. Hoboken, NJ, USA: Wiley, 2011.
- [11] Y. P. Gautam, "Password based circuit breaker with GSM module," *International Journal of Advanced Research, Ideas and Innovations in Technology*, vol. 3, no. 3, pp. 1460–1464, 2017.
- [12] T. Naruka, V. K. Sharma, V. Shingh, and S. V. Sharma, "Password-based circuit breaker," *Imperial Journal of Interdisciplinary Research (IJIR)*, vol. 3, no. 4, 2017.




- [13] M. Shoaib and V. Nagaraj, "Proteus based simulation of PV inverter for rural electrical service," *International Journal of Modern Engineering Research (IJMER)*, vol. 3, no. 2, pp. 1212-1219, 2013.
- [14] K. J. Ayala, *The 8051 microcontroller architecture, programming, and applications*. Eagan, MN, US: West Publishing Company, 1991.
- [15] M. A. Mazidi, J. G. Mazidi, and R. D. McKinlay, *The 8051 microcontroller and embedded systems*, Upper Saddle River, NJ, USA: Pearson Education, 2005.
- [16] R. G. Shriwastava, S. S. Hadpe, S. B. Patil, and M. P. Thakare, "The architecture of a 24 dynamic voltage restorer for voltage enhancement incorporating voltage vector methodologies," *Published in Elsevier Procedia*, 2021.
- [17] R. G. Shriwastava, S. Deshmukh, A. Tidke, and M. Thakre, "Comparative evaluation of control techniques of PMSM drive in automotive application," *Journal of Physics: Conference Series*, vol. 2062, p. 012024, 2021, doi: 10.1088/1742-6596/2062/1/012024.
- [18] R. G. Shriwastava, M. P. Thakre, K. V. Bhadane, M. S. Harne, and N. B. Wagh, "Performance enhancement of DCMLI fed DTC -PMSM drive in electric vehicle," *Bulletin of Electrical Engineering and Informatics (BEEI)*, vol. 11, no. 4, pp. 1867-1881, 2022, doi: 10.11591/eei.v11i4.3714.
- [19] M. P. Thakre and N. Kumar, "Evaluation and control perceptive of VSM-based multilevel PV-STATCOM for distributed energy system," *MAPAN*, vol. 36, pp. 561-578, 2021, doi: 10.1007/s12647-021-00481-x.
- [20] M. P. Thakre and A. Ahmad, "Interline power flow controller (IPFC) deployment in long transmission lines and its effects on distance relay," *Journal of The Institution of Engineers (India): Series B*, vol. 103, pp. 491-505, 2022, doi: 10.1007/s40031-021-00637-y.
- [21] R. G. Shriwastava, "Sensorless field oriented control of PMSM drive system for automotive application," *International Journal of Electric and Hybrid Vehicles*, vol. 8, no. 3, pp. 213-224, 2016, doi: 10.1504/IJEHV.2016.080015.
- [22] Y. Zhang, P. You, and L. Cai, "Optimal charging scheduling by pricing for EV charging station with dual charging modes," *IEEE Transactions on Intelligent Transportation Systems*, vol. 20, no. 9, pp. 3386-3396, Sept. 2019, doi: 10.1109/TITS.2018.2876287.
- [23] X. Ji, Z. Yin, Y. Zhang, X. Zhang, H. Gao, and X. Zhang, "Comprehensive pricing scheme of the EV charging station considering consumer differences based on integrated AHP/DEA methodology," *Mathematical Problems in Engineering*, vol. 2020, no. 1, p. 8657258, 2020, doi: 10.1155/2020/8657258.
- [24] H. Prasad, K. V. Bhadane, and P. Kumar, "Real-time performance evaluation of single phase 7 level Z-source boost inverter," in *7th International Conference on Electrical Energy Systems (ICEES)*, 2021, pp. 28-31, doi: 10.1109/ICEES51510.2021.9383751.
- [25] R. G. Shriwastava et al., "Performance analysis of conventional multilevel inverter driven PMSM drive in EV applications," *International Journal of Applied Power Engineering (IJAPE)*, vol. 14, no. 1, pp. 37-45, Mar. 2025, doi: 10.11591/ijape.v14.i1.pp37-45.

BIOGRAPHIES OF AUTHORS






Dr. Rakesh G. Shriwastava    obtained Ph.D. degree in Electrical Engineering specializing in power electronics and drives, from RTM Nagpur University (India) in 2017. He occupied various positions to serve the engineering institutes for about 24 years. He is currently working as a professor in the Department of Electrical Engineering, Govindrao Wanjari College of Engineering and Technology, Nagpur. His research interests include the analysis and control of electrical drives, particularly in hybrid and electric vehicle applications. He has several publications in national and international journals. He attended international and national conferences and also worked as a jury member. He is a member of professional bodies such as ISTE and IAENG. He can be contacted at email: rakesh_shriwastava@rediffmail.com.






Dr. Pawan C. Tapre    received the B.E. and M.E. degrees in Electrical Power System Engineering from Sant Gadge Baba Amravati University (SGBAU), Maharashtra, India, in 1995 and 2002 respectively, and Ph.D. degree in Electrical Engineering from Dr. C.V. Raman University (Dr. CVRU), Bilaspur, Chhattisgarh, India in 2022. Currently, he is an assistant professor at the Department of Electrical Engineering, S.N.D. College of Engineering and Research Center, Yeola (Nashik), and Maharashtra, India. His research interests include deregulated power systems, flexible AC transmission systems (FACTS), power systems, and power system protection. He can be contacted at email: pawan.tapre73@gmail.com.






Dr. Rajendra M. Rewatkar    obtained his B.E. degree in Electronics Engineering from RTM Nagpur University Nagpur, India in 1996. He received the M. Tech. degree in Electronics Engineering from G.H. Rasoni College of Engineering, Nagpur, India in 2010. He has been awarded doctoral degree in Electronics Engineering from RTM Nagpur University, Nagpur (India) in 2016. He occupied various positions to serve the engineering institutes for about 27 years. He is currently working as associate professor and head in Biomedical Engineering Department of Faculty of Engineering and Technology, Datta Meghe Institute of Higher Education and Research Sawangi (Meghe), Wardha. His research interests include signal processing and CMOS VLSI design. He is a fellow of IETE and life member of the professional bodies such as ISTE, IE, and IAENG. He can be contacted at email: rajendrarr.feat@dmier.edu.in.






Dr. Swapna M. Choudhary    is currently working as assistant professor in Electronics and Telecommunications Engineering of G. H. Rasoni College of Engineering, Nagpur. She has done her graduation in Electronics Engineering, post-graduation in VLSI and Ph.D. in Electronics Engineering from RTM, Nagpur University Nagpur. She is recipient of prestigious Lilawati Award by AICTE, Delhi. Her research areas are VANET, machine learning, and internet of things electronics communication. She has published several papers in reputed international conferences and journals. His research interests include signal processing and CMOS VLSI design. She has several publications in national and international journals. She attended international and national conferences. She can be contacted at email: swapna2k11@gmail.com.






Prof. Dr. Ramesh K. Rathod    working as an associate professor in the Department of Mechanical Engineering at PCET's Pimpri Chinchwad College of Engineering and Research, Ravet, Pune (M.S.), has about 23 years of teaching experience at the undergraduate and postgraduate levels. He was awarded Ph.D. in Mechanical Engineering from Rashtrasant Tukadoji Maharaj Nagpur University. He has filed 3 patents, 2 copyrights, published more than 12 research papers in reputed journals, and attended 10 international conferences. He can be contacted at email: ramesh.rathod@pccoer.in.






Prof. Dr. Sham H. Mankar    working as an associate professor in the Department of Mechanical Engineering at PCET's Pimpri Chinchwad College of Engineering and Research, Ravet, Pune (M.S.), has about 22 years of teaching experience at the undergraduate and postgraduate levels. He received his Ph.D. in Mechanical Engineering from Sant Gadge Baba Amravati University, Amravati. He has filed 4 patents, 2 copyrights, and 1 granted patent on his name, published more than 19 research papers in reputed journals, and attended 14 international conferences. He can be contacted at email: sham.mankar@pccoer.in.



Dr. Hemant R. Bhagat Patil    obtained Master and Ph.D. degrees in Mechanical Engineering from RTMNU, Nagpur (India). He occupied various positions to serve the engineering institutes for about 22 years. He is currently working as an associate professor in the Department of Mechanical, Govindrao Wanjari College of Engineering and Technology, Nagpur. He attended international and national conferences. He is a member of professional bodies such as ISTE. He can be contacted at email: hemant_bp@yahoo.com.



Dr. Salim A. Chavan    received B.E. degree from Government College of Engineering, SGB Amravati University, Amravati, in 1990 and M.E. degree from SGB Amravati University, Amravati, in 2008, all in Electronics and Telecommunication Engineering. He has done his Ph.D. in Video Processing (ETC) from Sant Gadge Baba Amravati University, Amravati in 2017. He occupied various positions to serve the engineering institutes for about 33 years. He is currently working as professor in the Department of Electronics and Telecommunication Engineering, Govindrao Wanjari College of Engineering and Technology, Nagpur. His research interest is in commutation system. He attended international and national conferences. He is a member of professional bodies ISTE. He can be contacted at email: salimsahil97@rediffmail.com.